

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

## S P E C I F I C A T I O N   P R O P O S A L

	Description	Weight Front	Weight Rear
<b>Price Level</b>			
	M2 PRL-27M (EFF:MY24 ORDERS)		
<b>Data Version</b>			
	SPECPRO21 DATA RELEASE VER 044		
<b>Vehicle Configuration</b>			
	M2 106 PLUS CONVENTIONAL CHASSIS	5,709	3,450
	2024 MODEL YEAR SPECIFIED		
	SET BACK AXLE - TRUCK		
	STRAIGHT TRUCK PROVISION, NON-TOWING		
	LH PRIMARY STEERING LOCATION		
<b>General Service</b>			
	TRUCK CONFIGURATION		
	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
	FIRE SERVICE		
	EMERGENCY VEHICLES BUSINESS SEGMENT		
	LIQUID BULK COMMODITY		
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
	MAXIMUM 8% EXPECTED GRADE		
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
	MEDIUM TRUCK WARRANTY		
	EXPECTED FRONT AXLE(S) LOAD : 14600.0 lbs		
	EXPECTED REAR DRIVE AXLE(S) LOAD : 26000.0 lbs		
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 40600.0 lbs		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
<b>Truck Service</b>		
FIRE TANK/PUMPER - MAIN DRIVELINE DRIVEN SPLIT-SHAFT PTO/PUMP ROSENBAUER EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0 in		
<b>Engine</b>		
CUM L9 360EV HP @ 2200 RPM, 2200 GOV RPM, 1150 LB-FT @ 1200 RPM, R/F/E	640	30
<b>Electronic Parameters</b>		
68 MPH ROAD SPEED LIMIT CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT PTO MODE ENGINE RPM LIMIT - 1200 RPM PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED PTO RPM WITH CRUISE SET SWITCH - 1200 RPM PTO RPM WITH CRUISE RESUME SWITCH - 1200 RPM PTO MODE CANCEL VEHICLE SPEED - 5 MPH PTO GOVERNOR RAMP RATE - 500 RPM PER SECOND FUEL DOSING OF AFTERTREATMENT ENABLED IN PTO MODE-CLEANS HYDROCARBONS AT HIGH TEMPERATURES ONLY ONE REMOTE PTO SPEED PTO SPEED 1 SETTING - 1200 RPM PTO MINIMUM RPM - 700 REGEN INHIBIT SPEED THRESHOLD - 5 MPH PTO 1, C/F PTO, NO SWITCH, TEM SUPPLIED REQUEST, FEEDBACK AND INTERLOCKS, WITH PTO CONNECTIONS, ENGAGE BEFORE DRIVING PTO 2, C/F PTO, NO SWITCH, TEM SUPPLIED REQUEST, FEEDBACK AND INTERLOCKS, WITH PTO CONNECTIONS, ENGAGE BEFORE DRIVING		
<b>Engine Equipment</b>		
2010 EPA/CARB/GHG21 CONFIGURATION NO 2008 CARB EMISSION CERTIFICATION STANDARD OIL PAN ENGINE MOUNTED OIL CHECK AND FILL		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
SIDE OF HOOD AIR INTAKE WITH NFPA COMPLIANT EMBER SCREEN AND FIRE RETARDANT DONALDSON AIR CLEANER		
DR 12V 275 AMP 40-SI BRUSHLESS PAD ALTERNATOR WITH REMOTE BATTERY VOLTAGE SENSE	10	
(2) DTNA GENUINE, FLOODED STARTING, MIN 2000CCA, 370RC, THREADED STUD BATTERIES	10	
BATTERY BOX FRAME MOUNTED		
STANDARD BATTERY JUMPERS		
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
NON-POLISHED BATTERY BOX COVER		
SMART BATTERY SHUT-OFF SWITCH		
PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS		
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
GVG, FIRE AND EMERGENCY SERVICE VEHICLES ENGINE WARNING		
CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF WITH BRAKE LAMPS	20	
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE EXITING FORWARD OF REAR TIRES	10	5
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH		
STANDARD EXHAUST SYSTEM LENGTH		
RH HORIZONTAL TAILPIPE, EXIT FORWARD OF REAR TIRES	20	20
6 GALLON DIESEL EXHAUST FLUID TANK		
100 PERCENT DIESEL EXHAUST FLUID FILL		
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
STANDARD DIESEL EXHAUST FLUID TANK CAP		
AIR POWERED ON/OFF ENGINE FAN CLUTCH		
AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED		
CUMMINS SPIN ON FUEL FILTER		
COMBINATION FULL FLOW/BYPASS OIL FILTER		
1100 SQUARE INCH ALUMINUM RADIATOR	70	
ANTIFREEZE TO -60F, ETHYLENE GLYCOL PRE- CHARGED SCA HEAVY DUTY COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
AUXILIARY ENGINE COOLING USING WATER FROM FIRE PUMP	10	
LOWER RADIATOR GUARD		
ALUMINUM FLYWHEEL HOUSING		
ELECTRIC GRID AIR INTAKE WARMER		
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH		
<b>Transmission</b>		
ALLISON 3000 EVS AUTOMATIC TRANSMISSION WITH PTO PROVISION	200	60
<b>Transmission Equipment</b>		
ALLISON VOCATIONAL PACKAGE 198 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODEL EVS		
ALLISON VOCATIONAL RATING FOR FIRE TRUCK/EMERGENCY VEHICLE APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES		
PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 5, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 5, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE ALTERNATE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED		
DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
PUMP MODE INPUT ENABLED 3RD/4TH LOCKUP WIRED ON TCM INPUT AJ/BQ - ALLISON 5TH GEN TRANSMISSIONS		
QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH BLUNTCUTS		
ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR		
(2) CUSTOMER INSTALLED MUNCIE CS10 SERIES PTO'S		
PTO MOUNTING, LH SIDE AND TOP RH SIDE OF MAIN TRANSMISSION ALLISON		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED		
TRANSMISSION PROGNOSTICS - ENABLED 2013		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

### Front Axle and Equipment

DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE	10
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	

**Prepared for:**  
 Heather Fox  
 ROSENBAUER AMERICA BB  
 100 3RD ST  
 LYONS, SD 57041  
 Phone: 605-543-5591

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
FIRE AND EMERGENCY SEVERE SERVICE, NON-ASBESTOS FRONT LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW TAS-85 POWER STEERING	40	
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE		
<b>Front Suspension</b>		
14,600# TAPERLEAF FRONT SUSPENSION	170	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
<b>Rear Axle and Equipment</b>		
RS-26-185 26,000# T-SERIES SINGLE REAR AXLE		255
4.56 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES		
MERITOR 16.5X7 P CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, CAST SHOES		20
FIRE AND EMERGENCY SEVERE SERVICE NON- ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)		
WEBB HEAVY WEIGHT CAST IRON REAR BRAKE DRUMS		80
REAR BRAKE DUST SHIELDS		5
REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		
HALDEX AUTOMATIC REAR SLACK ADJUSTERS		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE		
<b>Rear Suspension</b>		
26,000# FLAT LEAF SPRING REAR SUSPENSION WITH HELPER AND RADIUS ROD		170
SPRING SUSPENSION - NO AXLE SPACERS		
STANDARD AXLE SEATS IN AXLE CLAMP GROUP		
FORE/AFT CONTROL RODS		
<b>Brake System</b>		
AIR BRAKE PACKAGE		
WABCO 4S/4M ABS WITH TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
STD U.S. FRONT BRAKE VALVE		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
AIR DRYER MOUNTED INBOARD ON LH RAIL		
STEEL AIR TANKS MOUNTED AFT INSIDE AND/OR BELOW FRAME JUST FORWARD OF REAR SUSPENSION, NO TRIPLE OR TORPEDO TANKS		
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER ON ALL TANK(S)		
<b>Wheelbase &amp; Frame</b>		
4825MM (190 INCH) WHEELBASE		
11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	70	130
1900MM (75 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-20	90
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 124.41 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 121.41 in		
CALC'D FRAME LENGTH - OVERALL : 294.15 in		
CALCULATED FRAME SPACE LH SIDE : 89.69 in		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
CALCULATED FRAME SPACE RH SIDE : 71.81 in		
SQUARE END OF FRAME		
FRONT CLOSING CROSSMEMBER		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD CROSSMEMBER BACK OF TRANSMISSION		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REARMOST CROSSMEMBER		
STANDARD SUSPENSION CROSSMEMBER		
<b>Chassis Equipment</b>		
THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30	
FRONT TOW HOOKS - FRAME MOUNTED	15	
BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS		
GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
CHASSIS PREP FOR ROSENBAUER/CENTRAL STATES, MULTI-WHEELBASE, F/L SINGLE SPRING SUSPENSION, FORWARD 18 INCHES (450MM)		
3D STEP VEHICLE MODEL		
TANK BODY 0 TO 1500 GALLONS		
CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD		
<b>Fuel Tanks</b>		
50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH	20	
RECTANGULAR FUEL TANK(S)		
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
FUEL TANK(S) FORWARD		
PLAIN STEP FINISH		
FUEL TANK CAP(S)		
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR	-5	
EQUIFLO INBOARD FUEL SYSTEM		
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		



**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

	Description	Weight Front	Weight Rear
	FUEL COOLER MOUNTED LEFT HAND IN RAIL	10	
<b>Tires</b>			
	MICHELIN XZE 12R22.5 16 PLY RADIAL FRONT TIRES	50	
	MICHELIN XDN2 12R22.5 16 PLY RADIAL REAR TIRES		140
<b>Hubs</b>			
	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS		
	CONMET PRESET PLUS PREMIUM IRON REAR HUBS		
<b>Wheels</b>			
	ALCOA ULA18X 22.5X8.25 10-HUB PILOT 5.81 INSET ALUMINUM DISC FRONT WHEELS	-62	
	ALCOA ULA18X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS		-124
	POLISHED FRONT WHEELS; OUTSIDE ONLY		
	POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY		
	FRONT WHEEL MOUNTING NUTS		
	REAR WHEEL MOUNTING NUTS		
<b>Cab Exterior</b>			
	106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB		
	AIR CAB MOUNTING		
	CAB ROOF REINFORCEMENTS FOR ROOF MOUNTED COMPONENTS	2	
	LH AND RH EXTERIOR GRAB HANDLES WITH SINGLE RUBBER INSERT		
	HOOD MOUNTED CHROMED PLASTIC GRILLE		
	CHROME HOOD MOUNTED AIR INTAKE GRILLE		
	FIBERGLASS HOOD		
	HOOD LINER, ADDED FIREWALL AND FLOOR HEAT INSULATION	5	
	SINGLE ELECTRIC HORN		
	REAR LICENSE PLATE MOUNT END OF FRAME		
	INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL		
	LED AERODYNAMIC MARKER LIGHTS		
	DAYTIME RUNNING LIGHTS		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
OMIT STOP/TAIL/BACKUP LIGHTS AND PROVIDE WIRING WITH SEPARATE STOP/TURN WIRES TO 4 FEET BEYOND END OF FRAME		-5
STANDARD FRONT TURN SIGNAL LAMPS		
AUTOMATIC ON/OFF, ENGINE COMPARTMENT, HOOD ACTIVATED WORK LIGHT WITH MANUAL OVERRIDE	1	
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
RH DOWN VIEW MIRROR		
STANDARD SIDE/REAR REFLECTORS		
63X14 INCH TINTED REAR WINDOW		
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
RH AND LH ELECTRIC POWERED WINDOWS	4	
1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD		
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED		
<b>Cab Interior</b>		
PROFESSIONAL TRIM PACKAGE		
MIST AND CARBON CLOTH INTERIOR "PROFESSIONAL"		
CARBON WITH BASE BLACK ACCENT		
MOLDED PLASTIC DOOR PANEL		
MOLDED PLASTIC DOOR PANEL		
BLACK MATS WITH SINGLE INSULATION		
(1)DASH MOUNTED 12V POWER OUTLET		
(1)DASH MOUNTED DUAL 2.1 AMP USB-C CHARGER		
FORWARD ROOF MOUNTED CONSOLE		
LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS		
DIGITAL ALARM CLOCK IN DRIVER DISPLAY		
(2) CUP HOLDERS LH AND RH DASH		
M2/SD DASH		
5 LB. FIRE EXTINGUISHER	10	

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
HEATER, DEFROSTER AND AIR CONDITIONER		
STANDARD HVAC DUCTING		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
PREP KIT FOR CUSTOMER INSTALLED AUXILIARY HEATER, PLUMBING FROM ENGINE TO RAIL UNDER CAB WITH SHUTOFF VALVES		
STANDARD HEATER PLUMBING		
AUXILIARY HEATER PLUMBING		
VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR		
BINARY CONTROL, R-134A		
PREMIUM INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
PREMIUM LED CAB LIGHTING		
REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS	2	
ALL UNIT(S) KEYED ALIKE WITH CUSTOMER SPECIFIED KEY NUMBER FT1031		
KEY QUANTITY OF 2		
LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION		
TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB	10	
SEATS INC 911 UNIVERSAL SERIES HIGH BACK AIR SUSPENSION DRIVER SEAT WITH NFPA 1901-2009/2016 COMPLIANT SEAT SENSOR	50	
SEATS INC 911 UNIVERSAL SERIES HIGH BACK NON SUSPENSION PASSENGER SEAT WITH UNDERSEAT STORAGE AND NFPA 1901-2009/2016 COMPLIANT SEAT SENSOR	25	10
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
BLACK CORDURA PLUS CLOTH DRIVER SEAT COVER		
BLACK CORDURA PLUS CLOTH PASSENGER SEAT COVER		
NFPA 1901-2009 HIGH VISIBILITY ORANGE SEAT BELTS		
FIXED STEERING COLUMN		
4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
DRIVER AND PASSENGER INTERIOR SUN VISORS		
INTERFACE CONNECTORS AND WIRING FOR CUSTOMER PROVIDED LED STEP LIGHTING		
<b>Instruments &amp; Controls</b>		
DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY		
4 EXTRA PROGRAMMABLE SWITCHES/INDICATORS		
NO INSTRUMENT PANEL-DRIVER		
CONFIGURABLE LOWER PANEL WITH INTEGRATED UPPER STORAGE		
ENGINE REMOTE INTERFACE WITH PARK BRAKE AND NEUTRAL INTERLOCKS		
BLACK GAUGE BEZELS		
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM WITH (1) ADDITIONAL PARK SWITCH FOR CUSTOMER USE		
DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE		
ELECTRONIC AIR RESTRICTION INDICATOR DISPLAYED IN DRIVER DISPLAY		
ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS		
QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS		
QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS		
ENGINE REMOTE INTERFACE CONNECTOR AT POWERTRAIN INTERFACE CONNECTOR		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
DIGITAL TRANSMISSION OIL TEMPERATURE IN DRIVER DISPLAY		

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
WIRING PROVISION FOR CUSTOMER FURNISHED ROOF MOUNTED LIGHTBAR WITH 2 WIRES HANDLE UP TO 30 AMPS OF CURRENT		
PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE		
ELECTRIC ENGINE OIL PRESSURE GAUGE CENTER OVERHEAD INSTRUMENT PANEL BLANK		
QUICKFIT PROGRAMMABLE INTERFACE MODULE + (4) 20 AMP FUSED RELAYS	10	
NFPA VEHICLE DATA RECORDER AND SEATBELT DISPLAY		
STANDARD RADIO WIRING WITH STEERING WHEEL CONTROLS		
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
DETROIT CONNECT PLATFORM HARDWARE		
3 YEARS DAIMLER CONNECTIVITY BASE PACKAGE (FEATURES VARY BY MODEL) POWERED BY DETROIT CONNECT		
TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL		
IGNITION SWITCH CONTROLLED ENGINE STOP		
STEERING WHEEL MOUNTED ELECTRIC HORN CONTROL		
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
ALTERNATING FLASHING HEADLAMP SYSTEM WITH BODY BUILDER CONTROLLED ENGAGEMENT		

**Prepared for:**  
 Heather Fox  
 ROSENBAUER AMERICA BB  
 100 3RD ST  
 LYONS, SD 57041  
 Phone: 605-543-5591

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

	Description	Weight Front	Weight Rear
	ONE VALVE PARKING BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR  SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT  INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY		
<b>Design</b>			
	PAINT: ONE SOLID COLOR		
<b>Color</b>			
	CAB COLOR A: L0762EY MED RED ELITE EY BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT STANDARD E COAT/UNDERCOATING		
<b>Certification / Compliance</b>			
	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS		

## TOTAL VEHICLE SUMMARY

<b>Weight Summary</b>			
	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	7171 lbs	4336 lbs	11507 lbs
Total Weight <sup>+</sup>	7171 lbs	4336 lbs	11507 lbs

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

**Prepared for:**

Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591


**Prepared by:**

Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

Prepared for:  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

Prepared by:  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

## DIMENSIONS



## VEHICLE SPECIFICATIONS SUMMARY - DIMENSIONS

Model ..... M2106  
Wheelbase (545)..... 4825MM (190 INCH) WHEELBASE  
Rear Frame Overhang (552)..... 1900MM (75 INCH) REAR FRAME OVERHANG  
Fifth Wheel (578) ..... NO FIFTH WHEEL  
    Mounting Location (577) ..... NO FIFTH WHEEL LOCATION  
    Maximum Forward Position (in) ..... 0  
    Maximum Rearward Position (in)..... 0  
    Amount of Slide Travel (in) ..... 0  
    Slide Increment (in) ..... 0  
    Desired Slide Position (in)..... 0.0  
Cab Size (829) ..... 106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB  
Sleeper (682) ..... NO SLEEPER BOX/SLEEPER CAB  
Exhaust System (016)..... RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY  
WITH RH HORIZONTAL TAILPIPE EXITING FORWARD OF REAR TIRES

## TABLE SUMMARY - DIMENSIONS



**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com


Dimensions	Inches
Bumper to Back of Cab (BBC)	106.3
Bumper to Centerline of Front Axle (BA)	40.7
Front Axle to Back of Cab (AC)	65.6
Min. Cab to Body Clearance (CB)	3.0
Back of Cab to Centerline of Rear Axle(s) (CA)	124.4
Effective Back of Cab to Centerline of Rear Axle(s) (Effective CA)	121.4
Back of Cab Protrusions (Exhaust/Intake) (CP)	2.0
Back of Cab Protrusions (Side Extenders/Trim Tab) (CP)	0.0
Back of Cab Protrusions (CNG Tank)	0.0
Back of Cab Clearance (CL)	3.0
Back of Cab to End of Frame	199.2
Cab Height (CH)	67.5
Wheelbase (WB)	190.0
Frame Overhang (OH)	74.8
Overall Frame Length	294.2
Overall Length (OAL)	305.5
Rear Axle Spacing	0.0
Unladen Frame Height at Centerline of Rear Axle	41.9

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.

Prepared for:  
 Heather Fox  
 ROSENBAUER AMERICA BB  
 100 3RD ST  
 LYONS, SD 57041  
 Phone: 605-543-5591

Prepared by:  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

## TURNING RADIUS



## VEHICLE SPECIFICATIONS SUMMARY - TURNING RADIUS

Model ..... M2106  
 Cab Size (829) ..... 106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB  
 Wheelbase (545) ..... 4825MM (190 INCH) WHEELBASE  
 Front Tires (093) ..... MICHELIN XZE 12R22.5 16 PLY RADIAL FRONT TIRES  
     Width (in) ..... 11.4  
 Front Axle (400) ..... DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE  
     Kingpin Intersection (in) ..... 71.5  
 Bumper (556) ..... THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS  
     Width (in) ..... 93.5  
     Bumper Miter to Front Axle (in) ..... 21.458  
 Primary Steering Location (003) ..... LH PRIMARY STEERING LOCATION  
 Steering Gear (536) ..... TRW TAS-85 POWER STEERING  
     Dual Steering Gear ..... NONE  
     Ram ..... NONE  
 Rear Axle (420) ..... RS-26-185 26,000# T-SERIES SINGLE REAR AXLE  
 Axle Spacing (624) ..... NO AXLE SPACING

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.

**Prepared for:**  
Heather Fox  
ROSENBAUER AMERICA BB  
100 3RD ST  
LYONS, SD 57041  
Phone: 605-543-5591

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com